MoliCare® Premium Elastic

Application Tips

Having the right fit ensures comfort and leakage protection. Follow these tips to help get it right.



Ensure you have the right size and absorbency.

Measure at top of hip bone.

Note: you may need a different size than the MoliCare Premium Slip you were using.

	nip measurement	size
	70 - 90 cm	S
	85 - 120 cm	M
w C	115 - 145 cm	L
	140 - 175 cm	XL

ALIGNMENT


Ensure the pad is aligned equally at the front and the back.



USE THE WAVY LINES AS A GUIDE

Repeat with 2nd side panel.

Side panels should not crossover the wavy lines. If this occurs the pad may be too large and may leak. A smaller size should be considered. Give tabs a gentle rub to help with adhering.



PREPARE THE PAD


Fold and cup the pad to get it ready for application. This activates the leakage guards to prevent leakage.



LEG CUFFS TURNED OUT

Ensure leg cuffs are turned out and not covering the leakage guards.

If leakage guards are covered, leakage will occur.



ANGLE TABS DOWNWARDS

If the pad feels loose at the back, or is not fitting well, try applying the tabs at a downward angle to help conform to different body shapes.




CORRECT FITTING

Stand beside the person.

Slide the pad between the legs from the front to the back.


Ensure that the pad is centred in the right position by aligning the wetness indicator in line with the spine.



STRETCH THE SIDE PANELS

Fold out the 1st side panel and wrap around the person's hip.

Ensure the side panel is not too tight by placing a hand under the side panel when applying. Secure the adhesive tape into position.



View application videos and download resources at www.uslmedical.co.nz/molicare-elastics/







MoliCare® Premium Elastic

Application Tips

Having the right fit ensures comfort and leakage protection. Follow these tips to help get it right.



1 SIZ

SIZE

Ensure you have the right size and absorbency.

Measure at top of hip bone.


Note: you may need a different size than the MoliCare Premium Slip you were using.

	hip measurement	size
\	70 - 90 cm	S
	85 - 120 cm	M
W.	115 - 145 cm	L
	140 - 175 cm	XL

4

ALIGNMENT

Ensure the pad is aligned equally at the front and the back.




7

USE THE WAVY LINES AS A GUIDE

Repeat with 2nd side panel.

Side panels should not crossover the wavy lines. If this occurs the pad may be too large and may leak. A smaller size should be considered. Give tabs a gentle rub to help with adhering.



2

PREPARE THE PAD

Fold and cup the pad to get it ready for application. This activates the leakage guards to prevent leakage.



5

LEG CUFFS TURNED OUT

Ensure leg cuffs are turned out and not covering the leakage guards.

If leakage guards are covered, leakage will occur.



8

ANGLE TABS DOWNWARDS

If the pad feels loose at the back, or is not fitting well, try applying the tabs at a downward angle to help conform to different body shapes.



3

CORRECT FITTING

Turn the person to the recovery position and slide the pad between the legs from the front to the back. This helps align the pad and control hygiene.

Ensure that the pad is centred in the right position by aligning the wetness indicator in line with the spine and tuck the lower side panel under the hip. Turn the person onto their back.






6

STRETCH THE SIDE PANELS

Fold out the 1st side panel and wrap around the person's hip.

Ensure the side panel is not too tight by placing a hand under the side panel when applying. Secure the adhesive tape into position.



View application videos and download resources at www.uslmedical.co.nz/molicare-elastics/





